Easy and efficient pressure test of cylinder head and cylinder block coolant circuits.

Increased cradle and tank size to fit large diesel cylinder heads.

Quick and easy clamping system allowing tests at a pressure of 0 to 10 bars.

360° electric powered roll-over fixture.

Hydraulic cradle lift for easy positioning of heavy cylinder heads.

Stainless steel tank with heat barrier.

Heating elements: two changeover 4500 Watts elements.

Water level control.

Low voltage: 24V operating control.

Electronic adjustable thermostat.

Heating programmer: daily or weekly.

mmm I I Desou

0

0 0


0


SEROL

SERVICE QUALITY RELIABILITY

World Class Technology

TECHNICAL FEATURES		
Space requirements		
Length	mm/in	4050 / 160
Width	mm/in	2960 / 116
Height	mm/in	1800 / 70.9
Max cylinder head dimensi	ons	
Length	mm/in	1350 / 53.1
Width	mm	460 / 18.1
Height	mm	410 /16.1
Weight	Kg / lbs	300 / 660
Tank		
Tank capacity		710
Heating elements	kW	2x4.5
Thermostat	°C	0 - 90
Cylinder head clamping		
Hydraulic Hoist	kW	0.75
Gear-motor	kW	0.25
Rotational speed	rpm	4
Up and down stroke time	mm in 10 sec	600
Connections		
Power supply	16kVA-3x400V-AC-50/60 Hz or	
	16kVA-3x230V-AC-50/60 Hz	
Net weight approx. with empty tank	kg / lbs	685 / 1510





MACHINES SERDI S.A.

23, avenue des vieux moulins B.P. 380 74012 Annecy Cedex France

1 00 33 4 50 65 63 00

Fax: 00 33 4 50 52 99 92

www.serdi.com

Email: export@serdi.com

SERDI CORP.

1526 Litton Drive Stone mountain Georgia 30083 USA



(770) 493 82 20

Fax: (770) 493 83 23

Your distributor: